



**NOTES:**

- ① COMPACTED SUBGRADE
- ② 1/8" WIDE CONTROL JOINT WITH 3/4" MINIMUM DEPTH
- ③ ADAMS COUNTY TO DETERMINE REINFORCEMENT REQUIREMENTS IF REINFORCEMENT IS NEEDED
- ④ WHERE PAVEMENT IS TO BE RECONSTRUCTED CROWN SHALL BE TRANSITIONED OVER L/2' (MIN). NO CROWN SHALL EXIST AT THE CROSSPAN
- ⑤ COLD JOINTS SHALL BE DOWELED AS PER "D" (MINIMUM, 2 BARS). JOINT TO BE FILLED WITH JOINT FILLER
- ⑥ CONTRACTION JOINTS SHALL BE SPACED @ MAXIMUM 10' INTERVALS
- ⑦ CROSSPANS SHALL BE CONSTRUCTED IN HALVES TO ALLOW TRAFFIC MOVEMENT

ADAMS COUNTY TRANSPORTATION DEPARTMENT /ENGINEERING	<h2 style="margin: 0;">TYPICAL CROSSPAN</h2>	ADAMS COUNTY TRANSPORTATION DEPARTMENT /CONSTRUCTION INSPECTION
4430 S. ADAMS COUNTY PKWY. BRIGHTON, CO 80601	REVISION DATE: 06/02/14	FILE NAME: TYP_XPAN_D.DWG
		4430 S. ADAMS COUNTY PKWY. BRIGHTON, CO 80601